

## TX3716 2W Wire Wound High Precision Axial Resistor



# TX3716



### Electrical & Physical Specifications:

<b>A-Length:</b>	29.08mm (1.145")
<b>B-Diameter:</b>	11.10mm (.437")
<b>Lead Dimensions:</b>	.032" dia. X 1.500" long
<b>Max Watts @ 1% Tol:</b>	2
<b>Max Volts @ 1% Tol.:</b>	1250
<b>Temperature Range:</b>	-55°C. to +85°C
<b>Resistance (Ω):</b>	.5 Min. to 3.5 MEG Max.

### TX Series Engineering Attributes:

#### **RESISTANCE & TOLERANCES**

You can select any Ohmic value from .01Ω to 6MΩ (MegaOhm or MEG) with tolerances to ±.05%. For closer resistance tolerances refer to the Ultra Precision HR Series

#### **TCR CHARACTERISTIC**

Standard:  $0 \pm 10 \text{ ppm}/^\circ\text{C}$ . for **100Ω & higher**.

Standard:  $0 \pm 15 \text{ ppm}/^\circ\text{C}$ . for values **below 100Ω**

\*TCR is calculated between +25°C. & +100°C.

-For lower specific TCRs to  $\pm 1 \text{ ppm}/^\circ\text{C}$ ., please refer to the Ultra Precision HR Series to satisfy your specifications.

-For higher TCRs to  $\pm 6000 \text{ ppm}/^\circ\text{C}$ ., please refer to the Compensator Series to satisfy your specifications.

#### **POWER VS. AMBIENT TEMPERATURE**

All TX resistors are designed for full load based upon ±1% resistance tolerance providing the ambient temp (+) the rise in temp. due to self-heating, does not exceed +85°C. Refer to derating table below.

#### **STABILITY VS. TIME**

To ±.005%/yr. @ 25°C. with no load.

#### **REDUCTION OF THERMAL EMF USING COPPER TERMINALS:**

Less than ±3 microvolts/°C. emitted.

#### **PROTECTIVE SEAL**

Commercial plastic conforming coating.

#### **MARKING (Identification)**

PRC stamp, part type & name, Ω value & tolerance, physical size permitting.

#### **INDUCTANCE**

Std. TX resistors are inductively wound. Non-inductive windings are available, add suffix letter "N" in the part name.

**\*Please specify the ambient temperature span of your operation when placing your order.**

#### **Type TX Derating Table:\***

For ±1% resistance tolerance apply up to 100% of rated power to +85 Degrees Celsius.

For ±½% (0.5%) resistance tolerance apply up to 75% of rated power to +85 Degrees Celsius.

For  $\pm 1/4\%$  (0.25%) resistance tolerance apply up to 50% of rated power to +85 Degrees Celsius.

For  $\pm 1/10\%$  (0.1%) resistance tolerance apply up to 50% of rated power to +85 Degrees Celsius.

For  $\pm 1/20\%$  (0.05%) resistance tolerance apply up to 35% of rated power to +85 Degrees Celsius.

\* Percent of Rated Power vs. Combined Temp. of Self- Heating and Ambient (in °C).

### Details

SKU	TX3716
Type	Axial-Lead
Length	29.08mm (1.145")
Lead Dimensions	.032" dia. X 1.500" long
Diameter	11.10mm (.437")
TCR Char.	to $0 \pm 10 \text{ppm}/^\circ\text{C}$ . (between +25°C. and +100°C.)
Temperature	-55°C. to +85°C
Resistance	.5Ω to 3.5MegΩ
Tolerance	to $\pm .05\%$
Stability	to $\pm .005\%/yr.$ at +25°C
Max Watts	2
Max Volts	1250
Lead Free	Yes